

temperature, humidity, ambient noise, rain, wind, etc. The main problem is related to the heterogeneity of the technologies supported by the network nodes. To overcome this limitation, the low-cost collector, named Smart Gateway, acts as a transparent concentrator.

User-Environment interaction data collection.

Data related to elderly interaction with home appliances (TVs, appliances, etc.), cooking habits, and care of personal hygiene are important geriatric indicators useful to detect deviations from normal behavior and then highlight risk factors related to mental fragility.

The main peculiarity of the sensing network is its unobtrusiveness. Ambient parameters are gathered through sensors included in wearable devices. Indoor localization is achieved mainly through an unobtrusive wireless system based on the BLE technology, while outdoor positioning system is based on the GPS technology. Finally, indoor user-environment interaction is achieved by exploiting ad-hoc sensors, such as humidity sensor or gas sensor to detect cooking habits or smart devices, such as smart plugs in order to detect the use of TVs or appliances. All these devices are characterized by low cost of purchasing and management. To obtain reliable information about the user's interaction with the environment, data coming from ad-hoc sensors are combined with other information, e.g. localization data. For example, in order to deduce that the elderly is watching TV, at least two information are necessary, i.e. the power consumption measured by the smart plug that is connected to the TV plug and the presence of the user in the room. Similarly, to detect cooking habits, information coming from several sensors in the kitchen are combined with user's localization data.

B. Hardware components

Fig. 2 shows the Smart Gateway (Fig. 2.a) and the prototypes used in the validation scenario in order to emulate the wearable devices (Fig. 2.b and 2.c). The main actor of the sensing middleware scenario is the Smart Gateway, a data collector realized using a low cost Single Board Computer such as a




Fig. 2. Prototypes used in the validation scenario: a) Smart Gateway; b) and c) wearable devices.

Raspberry Pi [30]. The Smart Gateway performs various tasks, such as (i) data collection, (ii) data forwarding, and (iii) instructions forwarding from/to the SN. It has several input and output interfaces. In particular, the input interfaces are:

- Classic BT module: it is used to communicate with all classic BT devices;
- BLE module: it is used to communicate with all the BLE devices;
- The output interfaces used to forward the collected data are:
- Wi-Fi module: it allows the Internet access;
- Ethernet interface: installed on the Raspberry Pi board, it is used to realize a network connection via Ethernet cable.

In order to emulate the smart wristband worn by the elderly patient, two prototypal devices were realized. Fig. 2.b shows the first prototype used for the elderly indoor/outdoor localization. It was obtained by combining both Odroid [31] and Arduino [32] devices equipped with BLE, GPS and GPRS modules. This wearable device exploits the GPS technology for outdoor localization and BLE technology for indoor localization. The second prototype (Fig. 2.c) used for the detection of ambient parameters, was realized by using Nucleo Board [33] with MEMS and BLE shields [34]. In particular, MEMS shield is equipped with several sensors such as accelerometer, gyroscope, inertial modules, and environmental sensors.

The present work aims to define and test a prototype wearable device. It also may be replaced with a commercial product (e.g., the Sensor Tag [35]) that communicates values gathered from its sensors to the smartphone. By using these kind of commercial products it is possible to obtain similar results and preserve low-power and low-cost features.

V. SYSTEM VALIDATION

A. Proof of concept

In order to validate the proposed architecture from a functional point of view, a proof-of-concept approach has been used. In particular, the proposed scenario refers to the monitoring of an elderly in her/his home and in her/his outdoor daily activities. The elderly wears a smart device equipped with several MEMS such as accelerometers, gyroscopes, inertial modules, and environmental sensors. Another wearable device, exploiting the GPS and BLE technologies, provides indoor and outdoor localization functionalities. Furthermore, both wearable devices support data transmission capabilities. Fig. 3 shows a hypothetical indoor test scenario. A piBeacon, identified by a unique MAC address, is located in each room.



Fig. 3. Indoor test scenario.

The wearable devices operate as nodes of the SN, delivering several data to the Smart Gateway, placed in the indoor environment. Each piBeacon communicates its coordinates via BLE. The second wearable device constantly checks the presence of piBeacons and selects the nearest by comparing the Received Signal Strength Indicator (RSSI) of detected piBeacons.

An ad hoc implemented algorithm, running on the device, is responsible for maximizing the probability of selecting the closer piBeacon. By exploiting the RSSI, the wearable device computes a proximity index d , using the following formula:

$$RSSI = -(10n \log_{10} d + A) \quad (1)$$

where A is the received signal strength at 1 m, n is a signal propagation constant depending mainly on the environment, and d is the distance from the sender. The piBeacon with the lowest value of d represents the user's current indoor location. The indoor positional information is sent to the gateway (i.e., the elderly smartphone) through GPRS module.

When the patient leaves the indoor environment, by assuming that s/he wears the wristband, the GPS replaces the BLE module. The wearable device transmits the outdoor position retrieved by the GPS to the elderly smartphone via GPRS module, as in the case of the indoor localization.

Once received the elderly positions, the smartphone is responsible for formatting and sending these data to the CBB in order to make them available to the City4Age platform. Fig. 4 shows an example of the locomotor activity, with a detail of the room (Fig. 4.a) in which the elderly is detected and the position of the elderly in outdoor environment (Fig. 4.b), displayed by accessing to a localization Web server. In Fig. 5, a flow chart summarizes the main steps involved in the indoor/outdoor localization process.

Finally, the Smart Gateway may collect data from several environmental sensors measuring temperature, humidity,

pressure, etc. Environmental data and positional information could be used in order to generate commands and instructions




Fig. 5. Flow chart related to the indoor/outdoor positioning process.

addressed through the Smart Gateway to home devices in order to adapt the indoor environment to the needs of the elderly.

B. Validation of the indoor positioning feature

A further validation phase has been carried out in order to prove the effectiveness of the indoor positioning sub-systems.

First, a one-to-one mapping between BLE beacons and rooms has been considered, so that the room represents the granularity of the positioning algorithm. That said the correct user's localization has been tested in two different cases (Fig. 6). In the first case, referred as *best case*, the BLE devices of two consecutive rooms have been placed on the partition wall and not in line of sight of each other. In the second case, referred as *worst case*, the devices have been placed in line of sight at 5 meters from the separating door. The results shown in the Fig. 7 were obtained by positioning the wearable device (or smartphone) at three different distances from the door. The measurements allowed us to identify the Successful Localization Probability, which is the probability of correct localization of the user inside the room. The Fig. 7 shows how the results obtained are optimal in the best case and next to the ideal ones in the worst case.

VI. DISCUSSION

In order to demonstrate the effectiveness of the proposed architecture, it was compared with similar architectures proposed in the literature. In order to carry out this comparison, some parameters were selected, i.e., the recognized activities, the typical environment in which the system works, the complexity and cost of the system. In Table I, the results of this comparison are reported.



Fig. 4. Screenshots of localization system: a) indoor scenario b) outdoor scenario.




Fig. 6. Experimenting scenario of the positioning sub-system.

The main advantage of the proposed architecture is its ability to automatically recognizing behavioral changes in elderly people in an unobtrusive, low-cost and low-power modality. Furthermore, it guarantees hardware and technology




Fig. 7. Successful Localization Probability with the worst and best disposition of the BLE devices.

abstraction, since all low-level details are addressed by the adapter components included in the LEBB module, which provides as output a data object whose format is independent from any particular technology. At the same time, the proposed solution ensures high modularity and scalability, since any new technology can be added to the system simply by implementing the related adapter in LEBB. By doing so, any kind of raw data coming from heterogeneous devices can be properly handled by the system.

VII. CONCLUSION

This work proposes an architecture aimed to monitor elderly people in their daily life. It aims to support social/health services in dealing with mild cognitive impairments and frailty

TABLE I.
COMPARISON AMONG ELDERLY MONITORING ARCHITECTURES

	<i>Recognized activities</i>	<i>Typical environment</i>	<i>Complexity</i>	<i>Cost</i>
[23]	User-Environment interaction	Indoor	Medium/Low	Medium/High
[24]	Usage of medical devices	Indoor	Medium/High	Low
[25]	Locomotor activities	Indoor	Low	Low
[26]	Locomotor activities	Indoor/Outdoor	Medium/Low	Low
[27]	Fall	Indoor/Outdoor	Medium	Low
[28]	Fall	Indoor/Outdoor	Medium	Low
<i>Proposed architecture</i>	Indoor/Outdoor localization, Ambient parameters collection, User-Environment interaction	Indoor/Outdoor	Low	Low

in the elderly population. The proposed system is able to guarantee three important features: (i) continuous localization in both outdoor and indoor environment, (ii) continuous monitoring of ambient parameters, and (iii) continuous monitoring of appliances usage. The system is able to transparently collect sensor data coming from heterogeneous devices and forward them to the central repository within the City4Age platform through REST APIs. From here, by applying Big Data analytics, potential risky behaviors can be identified and highlighted.

As ongoing work, we are working to realize a low cost system able to both capture the elderly cooking habits and understand if s/he take care of her/his personal hygiene. This system exploits smart plugs and other sensors connected to a single-board computer (e.g., a Raspeberry Pi).

REFERENCES

- [1] J. M. Corchado, J. Bajo, and A. Abraham, "GerAmi: Improving Healthcare Delivery in Geriatric Residences," *IEEE Intelligent Systems*, vol. 23(2), 2008, pp. 19–25.
- [2] Yong Lin, Xingjia Lu, Fang Fang, and Jianbo Fan, "Personal Health Care Monitoring and Emergency Response Mechanisms," First Int. Symp. on Future Information and Communication Technologies for Ubiquitous HealthCare, Jinhua, 1-3 July 2013, pp. 1-5.
- [3] A. Lombardi, M. Ferri, G. Rescio, M. Grassi, and P. Malcovati, "Wearable Wireless Accelerometer with Embedded Fall-Detection Logic for Multi-Sensor Ambient Assisted Living Applications," *IEEE Sensors*, Christchurch, 25-28 Oct. 2009, pp. 1967-1970.
- [4] L. Meinel, M. Findeisen, M. Heß, A. Aplitzsch, and G. Hirtz, "Automated Real-Time Surveillance for Ambient Assisted Living Using an Omnidirectional Camera," *IEEE Int. Conf. on Consumer Electronics (ICCE)*, Las Vegas, NV, 10-13 Jan. 2014, pp. 396–399.
- [5] E. Kantoch, P. Augustyniak, M. Markiewicz, and D. Prusak, "Monitoring activities of daily living based on wearable wireless body sensor network," *36th Annual Int. Conf. of the IEEE Engineering in Medicine and Biology Society (EMBC)*, Chicago, IL, 26-30 Aug. 2014, pp. 586-589.

- [6] J. A. Uribe, J. F. Duitama, and N. G. Gómez, "Personalized Message Emission in a Mobile Application for Supporting Therapeutic Adherence," *13th Int. Conf. on e-Health Networking Applications and Services (Healthcom)*, Columbia, MO, 13-15 June 2011, pp. 15-20.
- [7] S. Vohnout, M. Engelman, and E. Enikov, "Miniature MEMS-based data recorder for prognostics and health management (PHM)," *IEEE AUTOTESTCON*, Orlando, FL, 13-16 Sept. 2010, pp. 1-8.
- [8] L. Mainetti, L. Patrono, and I. Sergi, "A survey on indoor positioning system," *Proc. of 22nd Int. Conf. on Software, Telecommunications and Computer Networks, SoftCOM 2014*, Split, 17-19 Sept. 2014, pp. 111-120.
- [9] Z. Zhongna, C. Xi, C. Yu-Chia, H. Zhihai, T. X. Han, and J. M. Keller, "Video-based activity monitoring for indoor environments," *IEEE Int. Symp. on Circuits and Systems*, Taipei, 24-27 May 2009, pp. 1449 – 1452.
- [10] B. Ausmeier, T. Campbell, and S. Berman, "Indoor Navigation Using a Mobile Phone," *African Conf. on Software Engineering and Applied Computing (ACSEAC)*, Gaborone, 24-26 Sept. 2012, pp. 109-115.
- [11] W. Elloumi et al., "Indoor navigation assistance with a Smartphone camera based on vanishing points," *Int. Conf. on Indoor Positioning and Indoor Navigation (IPIN)*, Montbéliard, France, 28-31 Oct. 2013, pp. 1-9.
- [12] D. Hauschildt and N. Kirchhof, "Advances in thermal infrared localization: Challenges and solutions," *Proc. of Int. Conf. on Indoor Positioning and Indoor Navigation (IPIN)*, 15-17 September 2010, pp. 1-8.
- [13] G. Monaci and A. Pandharipande, "Indoor user zoning and tracking in passive infrared sensing systems," *Proc. of European Signal Processing Conference (EUSIPCO)*, Bucharest, 27-31 August 2012, pp. 1089-1093.
- [14] L. Catarinucci, R. Colella, M. De Blasi, V. Mighali, L. Patrono, and L. Tarricone, "High performance RFID tags for item-level tracing systems," in *18th International Conference on Software, Telecommunications and Computer Networks, SoftCOM 2010*, Split-Bol (Croatia), 2010, pp. 21-26.
- [15] L. Xiaoming, P. Jing, and L. Tao, "A novel indoor localization system based on passive RFID technology," *Int. Conf. on Electronic and Mechanical Engineering and Information Technology (EMEIT)*, Harbin, Heilongjiang, 12-14 Aug. 2011, pp. 4285-4288.
- [16] L. Catarinucci, R. Colella, L. Mainetti, L. Patrono, S. Pieretti, I. Sergi, and L. Tarricone, "Smart RFID antenna system for indoor tracking and behavior analysis of small animals in colony cages," *IEEE Sensors Journal*, 14(4), 2014, pp. 1198-1206.
- [17] W. Yapeng, Y. Xu, Z. Yutian, L. Yue, and L. Cuthbert, "Bluetooth positioning using RSSI and triangulation methods," *IEEE Consumer Communications and Networking Conference (CCNC)*, Las Vegas, NV, 11-14 Jan. 2013, pp. 837-842.
- [18] S. Alletto, R. Cucchiara, G. Del Fiore, L. Mainetti, V. Mighali, L. Patrono, and G. Serra, "An Indoor Location-aware System for an IoT-based Smart Museum," *IEEE Internet of Things Journal*, vol. 3 (2), 2015, pp. 244-253. DOI: 10.1109/JIOT.2015.2506258
- [19] S. Kajioka, T. Mori, T. Uchiya, I. Takumi, and H. Matsuo, "Experiment of indoor position presumption based on RSSI of Bluetooth LE beacon," *IEEE 3rd Global Conf. on Consumer Electronics (GCCE)*, Tokyo, 7-10 Oct. 2014, pp. 337-339.
- [20] L. Mainetti, V. Mighali, L. Patrono, "A software architecture enabling the web of things," *IEEE Internet of Things Journal*, 2 (6), 2015, pp. 445-454.
- [21] L. Mainetti, L. Patrono, A. Secco, and I. Sergi, "An IoT-aware AAL system for elderly people," *1st International Multidisciplinary Conference on Computer and Energy Science, SpliTech 2016*, Split (Croatia), 13 July 2016.
- [22] "City4Age Project." [Online]. Available: <http://www.city4ageproject.eu/>. [Accessed: January 13, 2016].
- [23] L. Mainetti, L. Patrono and P. Rametta, "Capturing behavioral changes of elderly people through unobtrusive sensing technologies," *2016 24th International Conference on Software, Telecommunications and Computer Networks (SoftCOM)*, Split, Croatia, 2016, pp. 1-3. doi: 10.1109/SOFTCOM.2016.7772126
- [24] M. Fahim, I. Fatima, S. Lee, Y-K. Lee, "Daily life activity tracking application for smart homes using android smartphone", *IEEE 14th International Conference on Advanced Communication Technology (ICACT)*, pp. 241-245, 2012.
- [25] V. Villarreal, J. Fontecha, R. Hervás, J. Bravo, "Mobile and ubiquitous architecture for the medical control of chronic diseases through the use of intelligent devices: Using the architecture for patients with diabetes", *Future Generation Computer System*, vol. 34, pp. 161-175, 2014.
- [26] G. Villarrubia, J. Bajo, J. F. de Paz, and J. M. Corchado, "Monitoring and detection platform to prevent anomalous situations in home care," *Sensors*, vol. 14, no. 6, pp. 9900–9921, 2014.
- [27] J. Reyes-Ortiz, L. Oneto, A. Sam, A. Ghio, X. Parra, and D. Anguita, "Transition-Aware Human Activity Recognition Using Smartphones", *Neurocomputing*, vol. 171, 1 Jan. 2016, pp. 754–767.
- [28] M.B. Rasheed, N. Javaid, T. Ali Alghamdi, S. Mukhtar, U. Qasim, Z. Ali Khan, M.H.B. Raja, "Evaluation of Human Activity Recognition and Fall Detection Using Android Phone," *2015 IEEE 29th International Conference on Advanced Information Networking and Applications (AINA)*, 24-27 March 2015, pp. 163 - 170.
- [29] B. Aguiar, T. Rocha, J. Silva, I. Sousa, "Accelerometer-based fall detection for smartphones," *2014 IEEE International Symposium on Medical Measurements and Applications (MeMeA)*, 11-12 June 2014.
- [30] "Raspberry Pi." [Online]. Available: <https://www.raspberrypi.org/>. [Accessed: January 13, 2016].
- [31] "Odroid." [Online]. Available: <http://www.hardkernel.com/>. [Accessed: January 13, 2016].
- [32] "Arduino." [Online]. Available: <https://www.arduino.cc/>. [Accessed: January 13, 2016].
- [33] "Nucleo Board (STMicroelectronics)." [Online]. Available: <http://www.st.com/nucleoF401RE-pr>. [Accessed: January 13, 2016].
- [34] "Bluetooth low energy expansion board (STMicroelectronics)." [Online]. Available: <http://www.st.com/web/catalog/tools/FM116/SC1075/PF260517> [Accessed: January 13, 2016].
- [35] "TI Sensor Tag." [Online]. Available: http://www.ti.com/ww/en/wireless_connectivity/sensortag2015/?INTC=SensorTag&HQS=sensortag [Accessed: January 13, 2016].



Luca Mainetti is an Associate Professor of Software Engineering and Computer Graphics at the University of Salento. His research interests include web design methodologies, notations and tools, services oriented architectures and IoT applications, and collaborative computer graphics. He is a scientific coordinator of the GSA Lab - Graphics and Software Architectures Lab and IDA Lab - Identification Automation Lab at the Department of Innovation Engineering, University of Salento.



Luigi Patrono received his MS in Computer Engineering from University of Lecce, Lecce, Italy, in 1999 and PhD in Innovative Materials and Technologies for Satellite Networks from ISUFI-University of Lecce, Lecce, Italy, in 2003. He is an Assistant Professor of Network Design at the University of Salento, Lecce, Italy. His research interests include RFID, EPCglobal, Internet of Things, Wireless Sensor Networks, and design and performance evaluation of protocols. He is Organizer Chair of the international Symposium on RFID Technologies and Internet of Things within the IEEE SoftCOM conference. He is author of about 100 scientific papers published on international journals and conferences and four chapters of books with international diffusion.



Andrea Secco received the Master's degree in Computer Engineering with honors at the University of Salento, Lecce, Italy, in 2013. His thesis concerned the tracking of small laboratory animals, based on passive UHF RFID technology. Since June 2013 he collaborates with IDA Lab - Identification Automation Laboratory - at the Department of Innovation Engineering of the University of Salento. His activity is focused on the study of new tracking systems based on RFID technology in UHF band. He is also involved in the study of new solutions for indoor environments locating and tracking and development on new services based on NFC technology.



Ilaria Sergi received the Master's degree in Automation Engineering from the University of Salento, Lecce, Italy, in 2012. Her thesis focused on the tracking of small laboratory animals, based on passive UHF RFID technology. Since 2012, she has been with the IDA Laboratory and Identification Automation Laboratory, Department of Innovation Engineering, University of Salento. Her activity is focused on the study of new indoor tracking systems and homecare solutions. She has authored several papers on international journals and conferences.